

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: C0093
Product name: RINNOVA IN BARATTOLO
Chemical name and synonym: VERNICE ALCHIDICA ANTICORROSIVA
UFI: 2R50-U0YT-900X-YC6H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: VERNICE EFFETTO FERROMICACEO IN BARATTOLO.

1.3. Details of the supplier of the safety data sheet

Name: Talken Color Srl
Full address: via Don Milani 15
District and Country: 20025 Legnano (Mi)
Italia
Tel. 0331/579100
Fax 0331/579372
e-mail address of the competent person responsible for the Safety Data Sheet: tecnico@talkencolor.it

1.4. Emergency telephone number

For urgent inquiries refer to:
CAV “
Ospedale Pediatrico Bambino Gesù”
–
Roma
Tel. (+39) 06.6859.3726
CAV “
Azienda Ospedaliera Università di Foggia”
–
Foggia
Tel. 800.183.459
CAV “
Azienda Ospedaliera A. Cardarelli”
–
Napoli
Tel. (+39) 081.545.3333
CAV Policlinico “
Umberto I”
–
Roma
Tel. (+39) 06.4997.8000
CAV Policlinico “
A. Gemelli”
–
Roma
Tel. (+39) 06.305.4343
CAV Azienda Ospedaliera “
Careggi”
U.O. Tossicologia Medica –
Firenze

Tel. (+39) 055.794.7819
CAV Centro Nazionale di Informazione Tossicologica –
Pavia
Tel. (+39) 0382.24.444
CAV Ospedale Niguarda –
Milano
Tel. (+39) 02.66.1010.29
CAV Azienda Ospedaliera Papa Giovanni XXIII –
Bergamo
Tel. 800.88.33.00
CAV Centro Antiveleni Veneto –
Verona
Tel. 800.011.858

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P501 Dispose of contents in different containers for steel

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

Contains: BUTAN-1-OL
ACETONE
PROPAN-2-OL
N-BUTYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	Conc. %	Classification (EC) 1272/2008 (CLP)
ACETONE		
INDEX 606-001-00-8	24,639	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-2119471330-49-XXXX		
DIACETONE ALCOHOL		
INDEX 603-016-00-1	8,826	Flam. Liq. 3 H226, Eye Irrit. 2 H319, STOT SE 3 H335
EC 204-626-7		
CAS 123-42-2		
REACH Reg. 01-2119473975-21		
XYLENE		
INDEX 601-022-00-9	5,16	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

Talken Color Srl			Revision nr. 8
C0093 - RINNOVA IN BARATTOLO			Dated 10/04/2025
			Printed on 10/04/2025
			Page n. 4/23
Replaced revision:7 (Dated: 07/11/2024)			
CAS 1330-20-7			
REACH Reg. 01-2119488216-32-XXX			
PROPAN-2-OL			
INDEX 603-117-00-0	4,989	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336	
EC 200-661-7			
CAS 67-63-0			
REACH Reg. 01-2119457558-25			
N-BUTYL ACETATE			
INDEX 607-025-00-1	4,36	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066	
EC 204-658-1			
CAS 123-86-4			
REACH Reg. 01-2119485493-29			
BUTAN-1-OL			
INDEX 603-004-00-6	4,294	Flam. Liq. 3 H226, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336	
LD50 Oral: 790 mg/kg			
EC 200-751-6			
CAS 71-36-3			
REACH Reg. 01-2119484630-38			
bisortofosfato di trizinco			
INDEX 030-011-00-6	1,875	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1	
EC 231-944-3			
CAS 7779-90-0			
Miscela di reazione di o-xilene m-xilene, p-xilene etilbenzene			
INDEX -	1,423	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315	
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l, ATE Inhalation mists/powders: 1,5 mg/l			
EC 215-535-7			
CAS -			
REACH Reg. 01-2119488216-32-xxxx			
NAFTA SOLVENTE, AROMATICA LEGGERA			
INDEX -	1,2	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411	
EC 265-199-0			
CAS 64742-95-6			
NAPHTHA (PETROL.) HYDROTREATED HEAVY			
INDEX 649-327-00-6	1,2	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P	
EC 265-150-3			
CAS 64742-48-9			
REACH Reg. 01-2119463258-33-XXXX			
ETHYLBENZENE			
INDEX 601-023-00-4	0,939	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412	
LC50 Inhalation vapours: 17,2 mg/l/4h			
EC 202-849-4			
CAS 100-41-4			
REACH Reg. 01-2119489370-35-XXX			
2-BUTOXYETHANOL			

C0093 - RINNOVA IN BARATTOLO

INDEX 603-014-00-0 0,158 Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0 LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h
CAS 111-76-2
REACH Reg. 01-2119475108-36-XXXX
NONYLPHENOL, BRANCHED AND LINEAR, ETHOXYLATED (with average molecular weight \leq 1 540 g/mol)
INDEX 604-100-00-0 0,047 Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=10
EC 500-024-6
CAS 9016-45-9
TOLUENE
INDEX 601-021-00-3 0,001 Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9
CAS 108-88-3

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Avoid leakage of the product into the environment. Work in adequately ventilated areas. Avoid flames and sparks. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Keep the product in clearly labelled containers. Keep containers well sealed. Avoid contact with water or that may absorb moisture at all costs. Avoid violent blows. Avoid overheating. Store in a ventilated and dry place, far away from sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

ESP	España	Límites de exposición profesional para agentes químicos en España 2023
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

ACETONE					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	1210	500		
VLEP	ITA	1210	500		
WEL	GBR	1210	500	3620	1500
OEL	EU	1210	500		
TLV-ACGIH			250		500

DIACETONE ALCOHOL					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	241	50		
WEL	GBR	241	50	362	75

Talken Color Srl						Revision nr. 8
C0093 - RINNOVA IN BARATTOLO						Dated 10/04/2025
						Printed on 10/04/2025
						Page n. 8/23
						Replaced revision:7 (Dated: 07/11/2024)
TLV-ACGIH23850						
XYLENE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			
PROPAN-2-OL						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	500	200	1000	400	
WEL	GBR	999	400	1250	500	
TLV-ACGIH			492200983400			
N-BUTYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	241	50	723	150	
VLEP	ITA	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50150			
BUTAN-1-OL						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	61	20	154	50	
WEL	GBR			154	50	SKIN
TLV-ACGIH			6120			
NAFTA SOLVENTE, AROMATICA LEGGERA						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH				32INHAL		
ETHYLBENZENE						
Threshold Limit Value						

Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	441	100	884	200
VLEP	ITA	442	100	884	200
WEL	GBR	441	100	552	125
OEL	EU	442	100	884	200
TLV-ACGIH		87	20		
2-BUTOXYETHANOL					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	98	20	245	50
VLEP	ITA	98	20	246	50
WEL	GBR	123	25	246	50
OEL	EU	98	20	246	50
TLV-ACGIH		97	20		
TOLUENE					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	192	50	384	100
VLEP	ITA	192	50		
WEL	GBR	191	50	384	100
OEL	EU	192	50	384	100
TLV-ACGIH			20		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	as showed in color folder	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	> 35 °C	
Flammability	not applicable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 23 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not applicable	
Solubility	solubile in acetone e/o diluente nitro	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	25,18 %
VOC (Directive 2010/75/EU)	56,07 %
Explosive properties	not applicable
Oxidising properties	not applicable

SECTION 10. Stability and reactivity**10.1. Reactivity**

The product can decompose and/or react violently.

ACETONE

Decomposes under the effect of heat.

DIACETONE ALCOHOL

Decomposes at temperatures above 90°C/194°F.

N-BUTYL ACETATE

Decomposes on contact with: water.

BUTAN-1-OL

Attacks various types of plastic materials.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

TOLUENE

Avoid exposure to: light.

10.2. Chemical stability

See previous paragraph.

10.3. Possibility of hazardous reactions

See paragraph 10.1.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

DIACETONE ALCOHOL

Risk of explosion on contact with: air,sources of heat.May react dangerously with: alkaline metals,amines,oxidising agents,acids.

XYLENE

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

BUTAN-1-OL

Reacts violently developing heat on contact with: aluminium,strong oxidising agents,strong reducing agents,hydrochloric acid.Forms explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants.Attacks various types of plastic materials.May form explosive mixtures with: air.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

10.4. Conditions to avoid

As the product decomposes even at ambient temperature, it must be stored and used at a controlled temperature. Avoid violent blows.

ACETONE

Avoid exposure to: sources of heat,naked flames.

DIACETONE ALCOHOL

Avoid exposure to: light,sources of heat,naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

BUTAN-1-OL

Avoid exposure to: sources of heat,naked flames.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

ACETONE

Incompatible with: acids,oxidising substances.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes,irritant substances.

ETHYLBENZENE

May develop: methane,styrene,hydrogen,ethane.

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

DIACETONE ALCOHOL

WORKERS: inhalation; contact with the skin.

XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

C0093 - RINNOVA IN BARATTOLO**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**DIACETONE ALCOHOL**

Acute toxicity causes irritation of the eyes, nose and throat in humans at 100 ppm (476 mg/kg) and pulmonary disorders at 400 ppm. No chronic effects on humans have been reported. The substance may have a depressive effect on the respiratory centres and cause death from respiratory failure.

XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (IspeSI). Is irritating for skin, conjunctiva and respiratory tract.

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects**XYLENE**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

DIACETONE ALCOHOL

LD50 (Oral):	4000 mg/kg Rat
--------------	----------------

C0093 - RINNOVA IN BARATTOLO**XYLENE**

LD50 (Dermal):	4350 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

PROPAN-2-OL

LD50 (Dermal):	12800 mg/kg Rat
LD50 (Oral):	4710 mg/kg Rat
LC50 (Inhalation vapours):	72,6 mg/l/4h Rat

N-BUTYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

BUTAN-1-OL

LD50 (Dermal):	3400 mg/kg Rabbit
LD50 (Oral):	790 mg/kg Rat
LC50 (Inhalation vapours):	8000 ppm/4h Rat

Miscela di reazione di o-xilene m-xilene, p-xilene etilbenzene

ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation mists/powders):	1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

NAPHTHA (PETROL.) HYDROTREATED HEAVY

LD50 (Dermal):	> 2000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat

ETHYLBENZENE

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

2-BUTOXYETHANOL

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat

NONYLPHENOL, BRANCHED AND LINEAR, ETHOXYLATED (with average molecular weight \leq 1 540 g/mol)

LD50 (Dermal):	1780 mg/kg Rabbit
LD50 (Oral):	1310 mg/kg Rat

TOLUENE

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

C0093 - RINNOVA IN BARATTOLO

NAPHTHA (PETROL.) HYDROTREATED
HEAVY

LC50 - for Fish	8,2 mg/l/96h Pimephales promelas
EC50 - for Crustacea	4,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h Pseudokirchnerella subcapitata

bisortofosfato di trizinco

LC50 - for Fish	0,9 mg/l/96h
-----------------	--------------

12.2. Persistence and degradabilityNONYLPHENOL, BRANCHED AND
LINEAR, ETHOXYLATED (with average
molecular weight $\leq 1\ 540$ g/mol)
Solubility in water

> 10000 mg/l

Rapidly degradable
XYLENE

Solubility in water	100 - 1000 mg/l
---------------------	-----------------

Rapidly degradable
TOLUENE

Solubility in water	100 - 1000 mg/l
---------------------	-----------------

Rapidly degradable
ETHYLBENZENE

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

Rapidly degradable
BUTAN-1-OL

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

Rapidly degradable
2-BUTOXYETHANOL

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

Rapidly degradable
DIACETONE ALCOHOL

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

Rapidly degradable
PROPAN-2-OLRapidly degradable
ACETONERapidly degradable
N-BUTYL ACETATE

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

NAPHTHA (PETROL.) HYDROTREATED
HEAVY

Rapidly degradable

12.3. Bioaccumulative potentialNONYLPHENOL, BRANCHED AND
LINEAR, ETHOXYLATED (with average
molecular weight $\leq 1\ 540$ g/mol)
Partition coefficient: n-octanol/water

3,7

XYLENE

Partition coefficient: n-octanol/water	3,12
--	------

C0093 - RINNOVA IN BARATTOLO

BCF 25,9

TOLUENE

Partition coefficient: n-octanol/water 2,73

BCF 90

ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

BUTAN-1-OL

Partition coefficient: n-octanol/water 1

BCF 3,16

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

DIACETONE ALCOHOL

Partition coefficient: n-octanol/water -0,09

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33

Limited

Tunnel

IMDG:	Special provision: 163, 367, 640C, 650 EMS: F-E, <u>S-E</u>	Quantities: 5 lt	restriction code: (D/E)
		Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>			
Point	3 - 40		
<u>Contained substance</u>			
Point	75		
Point	46a	NONYLPHENOL, BRANCHED AND LINEAR, ETHOXYLATED (with average molecular weight ≤ 1 540 g/mol)	

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor
The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.
All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.

C0093 - RINNOVA IN BARATTOLO

H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)

C0093 - RINNOVA IN BARATTOLO

- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01.